

ICE

INTERNATIONAL CONSTRUCTION EQUIPMENT

VIBRATORY HAMMER PRODUCT RANGE

FREE HANGING
VIBRATORY HAMMERS



EXCAVATOR MOUNTED
VIBRATORY HAMMERS



GÁNDARA

SU EQUIPO EN CIMENTACIÓN

VIBRATORY HAMMERS EXCAVATOR MOUNTED

| | 230B | 328B | 428B | 528B |
|-------------------------|-------------------|-------------------|-------------------|-------------------|
| Eccentric moment | 2.2 | 3.2 | 4.0 | 5.6 |
| Max. frequency | 3000 | 2800 | 2800 | 2800 |
| Max. centrifugal force | 220 | 275 | 344 | 481 |
| Max. line pull capacity | 120 | 120 | 120 | 120 |
| Max. hydr. power | 53/72 | 65/88 | 98/133 | 98/133 |
| Max. oil flow | 90 | 110 | 170 | 170 |
| Total weight | 1080 | 1090 | 1280 | 1290 |
| Max. amplitude | 6.1 | 8.6 | 8.9 | 10.9 |
| L x W x H | 1128 x 520 x 1416 | 1128 x 520 x 1416 | 1128 x 646 x 1502 | 1128 x 646 x 1502 |
| Recommended clamp | 40TU | 40TU | 60TU | 60TU |

| | 625B | 823B | 1223B |
|-------------------------|-------------------|-------------------|-------------------|
| Eccentric moment | 6.0 | 8.0 | 11.5 |
| Max. frequency | 2500 | 2300 | 2300 |
| Max. centrifugal force | 411 | 465 | 670 |
| Max. line pull capacity | 120 | 120 | 180 |
| Max. hydr. power | 117/159 | 108/147 | 190/258 |
| Max. oil flow | 201 | 185 | 326 |
| Total weight | 1300 | 1310 | 2380 |
| Max. amplitude | 12.9 | 17.2 | 12.8 |
| L x W x H | 1128 x 646 x 1502 | 1128 x 646 x 1502 | 1540 x 435 x 1870 |
| Recommended clamp | 60TU | 60TU | 100TU |

