

ICE

INTERNATIONAL CONSTRUCTION EQUIPMENT

VIBRATORY HAMMER PRODUCT RANGE

FREE HANGING
VIBRATORY HAMMERS



EXCAVATOR MOUNTED
VIBRATORY HAMMERS




GÁNDARA

SU EQUIPO EN CIMENTACIÓN


VIBRATORY HAMMERS RESONANCE FREE EXCAVATOR MOUNTED

6RFB




Eccentric moment	kgm	0 - 6.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 380
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	80/110
Max. oil flow	L/min	138
Total weight	kg	1490
Max. amplitude	mm	10.6
L x W x H	mm	1158 x 595 x 1711
Recommended clamp		60TU

6RFSH




Eccentric moment	kgm	0 - 6.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 380
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	80/110
Max. oil flow	L/min	138
Total weight	kg	1900
Max. amplitude	mm	10.6
L x W x H	mm	1750 x 848 x 1662
Recommended clamp		60TU

8RFB




Eccentric moment	kgm	0 - 7.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 435
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	108/147
Max. oil flow	L/min	185
Total weight	kg	1510
Max. amplitude	mm	12.1
L x W x H	mm	1158 x 595 x 1711
Recommended clamp		60TU

8RFSH



Eccentric moment	kgm	0 - 7.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 435
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	108/147
Max. oil flow	L/min	185
Total weight	kg	1930
Max. amplitude	mm	12.1
L x W x H	mm	1750 x 848 x 1662
Recommended clamp		60TU

11RFB



Eccentric moment	kgm	0 - 11
Max. frequency	rpm	2350
Max. centrifugal force	kN	0 - 665
Max. line pull capacity	kN	180
Max. hydr. power	kW/HP	189/254
Max. oil flow	L/min	323
Total weight	kg	2225
Max. amplitude	mm	11.5
L x W x H	mm	1572 x 506 x 2143
Recommended clamp		100TU

