

ICE

INTERNATIONAL CONSTRUCTION EQUIPMENT

VIBRATORY HAMMER PRODUCT RANGE

FREE HANGING
VIBRATORY HAMMERS




EXCAVATOR MOUNTED
VIBRATORY HAMMERS



GÁNDARA
SU EQUIPO EN CIMENTACIÓN


VIBRATORY HAMMERS RESONANCE FREE

6RF




Eccentric moment	kgm	0 - 6.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 377
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	80/109
Max. oil flow	L/min	138
Total weight	kg	1735
Max. amplitude	mm	10.6
L x W x H	mm	1530 x 595 x 2000
Recommend. power pack		200 series
Recommended clamp		60TU

8RF




Eccentric moment	kgm	0 - 7.5
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 435
Max. line pull capacity	kN	120
Max. hydr. power	kW/HP	108/147
Max. oil flow	L/min	185
Total weight	kg	1765
Max. amplitude	mm	12.1
L x W x H	mm	1530 x 595 x 2000
Recommend. power pack		200 series
Recommended clamp		60TU

11RFs




Eccentric moment	kgm	0 - 11.0
Max. frequency	rpm	2350
Max. centrifugal force	kN	0 - 679
Max. line pull capacity	kN	180
Max. hydr. power	kW/HP	140/190
Max. oil flow	L/min	240
Total weight	kg	2225
Max. amplitude	mm	11.5
L x W x H	mm	1800 x 446 x 2430
Recommend. power pack		200 series
Recommended clamp		100TU

11RF




Eccentric moment	kgm	0 - 11.0
Max. frequency	rpm	2350
Max. centrifugal force	kN	0 - 679
Max. line pull capacity	kN	180
Max. hydr. power	kW/HP	189/257
Max. oil flow	L/min	323
Total weight	kg	2225
Max. amplitude	mm	11.5
L x W x H	mm	1800 x 446 x 2430
Recommend. power pack		400 series
Recommended clamp		100TU

14RF




Eccentric moment	kgm	0 - 14.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 810
Max. line pull capacity	kN	240
Max. hydr. power	kW/HP	213/290
Max. oil flow	L/min	375
Total weight	kg	3910
Max. amplitude	mm	9.5
L x W x H	mm	1854 x 590 x 2738
Recommend. power pack		400 series
Recommended clamp		100TU

18RF




Eccentric moment	kgm	0 - 18.0
Max. frequency	rpm	2100
Max. centrifugal force	kN	0 - 870
Max. line pull capacity	kN	240
Max. hydr. power	kW/HP	198/269
Max. oil flow	L/min	340
Total weight	kg	3920
Max. amplitude	mm	11.6
L x W x H	mm	1854 x 590 x 2738
Recommend. power pack		400 series
Recommended clamp		130TU

18RF-Ts




Eccentric moment	kgm	0 - 18.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 1044
Max. line pull capacity	kN	240
Max. hydr. power	kW/HP	292/397
Max. oil flow	L/min	501
Total weight	kg	4120
Max. amplitude	mm	11.6
L x W x H	mm	1854 x 590 x 2738
Recommend. power pack		600 series
Recommended clamp		130TU

28RFs




Eccentric moment	kgm	0 - 28.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 1624
Max. line pull capacity	kN	400
Max. hydr. power	kW/HP	321/437
Max. oil flow	L/min	550
Total weight	kg	6500
Max. amplitude	mm	11.0
L x W x H	mm	2390 x 552 x 3376
Recommend. power pack		600 series
Recommended clamp		200TU

28RF




Eccentric moment	kgm	0 - 28.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 1624
Max. line pull capacity	kN	500
Max. hydr. power	kW/HP	431/586
Max. oil flow	L/min	740
Total weight	kg	7100
Max. amplitude	mm	11.0
L x W x H	mm	2647 x 552 x 3376
Recommend. power pack		900 series
Recommended clamp		200TU

36RF-Ts




Eccentric moment	kgm	0 - 36.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 2080
Max. line pull capacity	kN	500
Max. hydr. power	kW/HP	591/804
Max. oil flow	L/min	1013
Total weight	kg	8400
Max. amplitude	mm	11.3
L x W x H	mm	2647 x 552 x 3376
Recommend. power pack		1000 series
Recommended clamp		320TU

46RF



Eccentric moment	kgm	0 - 46.0
Max. frequency	rpm	2300
Max. centrifugal force	kN	0 - 2669
Max. line pull capacity	kN	800
Max. hydr. power	kW/HP	671/913
Max. oil flow	L/min	1150
Total weight	kg	9200
Max. amplitude	mm	12.3
L x W x H	mm	2770 x 1080 x 3984
Recommend. power pack		1200 series
Recommended clamp		320TU

64RF



Eccentric moment	kgm	0 - 64.0
Max. frequency	rpm	1950
Max. centrifugal force	kN	0 - 2669
Max. line pull capacity	kN	800
Max. hydr. power	kW/HP	683/929
Max. oil flow	L/min	1170
Total weight	kg	9500
Max. amplitude	mm	17.1
L x W x H	mm	2770 x 1080 x 3984
Recommend. power pack		1200 series
Recommended clamp		320TU